



G3 Admix 7

Description:

Wagman G3 Admix 7 is an admixture for all concrete applications. Engineered with Nano infused cements Admix 7 achieves full dispersal in the concrete matrix. Admix 7 brings out the best qualities in concrete by reducing permeability, increasing strengths, abrasion resistance and reducing shrinkage.

In certain applications Admix 7 use has shown that overall cementitious content can be decreased while meeting specified standards. Other possibilities include using Admix 7 to achieve strength sooner allowing the project timeline to accelerate.

Features & Benefits:

Internal Curing Properties
Reduced Shrinkage and cracking
Reduces concrete permeability
Better freeze/thaw resistance
Eliminates traditional water cure or curing compounds
Reduces effects of premature evaporation from wind or low humidity
Increased pozzolanic reaction conditions Portland Type 1L Cement
Reactive with Type C and Type F Fly Ash

Applications:

Interior slabs on grade
Slabs to be polished
Elevated slabs
Exterior pavement
Structural walls
Columns
Footings
Roadways
Site work- Sidewalks, curbs
Parking Garages
Decorative Concrete

Dosage:

Admix 7 may be dosed at 2 ounces to 12 ounces per 100/weight of total cementitious material. Typical applications range from 5 ounces to 10 ounces per 100/ weight

Mixing:

Admix 7 may be added at any time during the process of creating concrete. Best practice is to add desired amount of Admix 7 after all dry materials, but before final balance of mix design allowable water is added to mix.

Standard dispensing equipment for water-based admixtures may be used.

Packaging:

717.854.2120



info@wagman.us



WAGMAN G3



Volume

5 Gallons
55 Gallons
275 Gallons
Bulk

Pail

Drum
Tote

Storage, Handling, and Transport

Admix 7 is a water based admix- Do not allow to freeze
Transport and store between 40-95 degrees Fahrenheit
Keep container sealed
Properly stored Admix 7 has a shelf life of 12 months

Technical Support

Technical support is available from the manufacturer. Call 717.854.2120 and ask for G3 technical support.

Warning & Safety

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE ENTIRE SAFETY DATA SHEET. Safety Data Sheets (SDS) are available at www.wagman.us or by request by calling 717.854.2120

Warranty

Wagman Metal Products are warranted to be of uniform quality, within manufacturing tolerances and to meet the technical properties on the current product data sheet. The information is believed to be reliable. This information contained in this bulletin is based on knowledge, experience and testing with the materials used in production of Wagman Metal products. Applicator is responsible for testing material for effectiveness and performance. The application of Wagman products is employed by the customer who is outside the control of Wagman Metal Products. Wagman is not liable or responsible for any loss, damage or injury from the use or application of any Wagman products. Wagman Metal's liability under this product warranty shall be limited to a refund of purchase price or replacement of the product. Wagman Metal shall have no liability for any loss of use, interruption of business, lost profits, or goodwill, or for any special, incidental, or consequential damages of any kind arising from the purchase or use of the warranted product. Any claim made under this warranty must be made within one (1) year of the date of purchase and shall be accompanied by any reports or test results that form the warranty claim. No warranty is made that the use of such information or our product will not infringe upon any patent. No representative or distributor is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Wagman Metal shall have the right, but not the obligation to conduct site inspections and perform tests pertaining to the claim. Sole remedy shall be replacement of product proven defective.

