



G3 FP Ultimate Seal

Description:

Wagman G3 FP Ultimate Seal is a penetrating stain resistor for polished concrete surfaces. Ultimate Seal works inside the surface of the concrete to repel oil and water.

Features & Benefits:

Excellent for Polished Concrete applications
Superior resistance to water, oil, and food stains
High coverage rate
Non film forming- does not trap moisture
Increases long term durability
Does not yellow or blush
Will not chip, peel, or flake

Applications:

Polished Concrete
Interior slabs on grade
Restaurants/ Office/ Grocery/ Retail

Coverage:

1200-2000 square feet per gallon

Application:

Protect all adjacent surfaces
Confirm surface is free of dirt, oil or any barrier that will stop product from penetrating
Apply to dry surface
Pre-Test a small area to confirm desired results
Application methods may vary based on jobsite conditions- Typical application is with low pressure sprayer and microfiber pad
Wet microfiber pad with G3 FP Ultimate Seal
Apply in light spray
Work in with Microfiber
Maintain a wet edge
Allow treated surface to dry
High Speed burnish to remove any haze with white pad
Clean tools and equipment with water

Packaging:

Volume

5 Gallons	Pail
55 Gallons	Drum
275 Gallons	Tote
Bulk	

Storage, Handling, and Transport

717.854.2120



info@wagman.us



WAGMAN G3



Do not allow to freeze
Transport and store between 40-95 degrees Fahrenheit
Protect from UV exposure
Keep container sealed
Properly stored G3 FP Ultimate Seal has a shelf life of 12 months

Technical Support

Technical support is available from the manufacturer. Call 717.854.2120 and ask for G3 technical support.

Warning & Safety

KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY. BEFORE USING THIS PRODUCT PLEASE READ THE ENTIRE SAFETY DATA SHEET. Safety Data Sheets (SDS) are available at www.wagman.us or by request by calling 717.854.2120

Warranty

Wagman Metal Products are warranted to be of uniform quality, within manufacturing tolerances and to meet the technical properties on the current product data sheet. The information is believed to be reliable. This information contained in this bulletin is based on knowledge, experience and testing with the materials used in production of Wagman Metal products. Applicator is responsible for testing material for effectiveness and performance. The application of Wagman products is employed by the customer who is outside the control of Wagman Metal Products. Wagman is not liable or responsible for any loss, damage or injury from the use or application of any Wagman products. Wagman Metal's liability under this product warranty shall be limited to a refund of purchase price or replacement of the product. Wagman Metal shall have no liability for any loss of use, interruption of business, lost profits, or goodwill, or for any special, incidental, or consequential damages of any kind arising from the purchase or use of the warranted product. Any claim made under this warranty must be made within one (1) year of the date of purchase and shall be accompanied by any reports or test results that form the warranty claim. No warranty is made that the use of such information or our product will not infringe upon any patent. No representative or distributor is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Wagman Metal shall have the right, but not the obligation to conduct site inspections and perform tests pertaining to the claim. Sole remedy shall be replacement of product proven defective.